



## MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC.

**NU PORCE APPLIANCE TOUCH UP  
ALMOND  
ITEM #12008**

### HAZARDOUS MATERIAL INFORMATION SYSTEM

HEALTH	1
--------	---

FLAMMABILITY	0
--------------	---

REACTIVITY	0
------------	---

PROTECTIVE EQUIPMENT	A
----------------------	---

(HAZARD RATING: 0=LEAST, 1=SLIGHT, 2=MODERATE, 3=HIGH,  
4=EXTREME) (A=SAFETY GLASSES)

### SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME:  
HOMAX PRODUCTS, INC.  
468 W. HORTON RD.  
BELLINGHAM WA 98226

#### 24 HOUR EMERGENCY PHONE NUMBER:

CHEMTREC 1-800-424-9300

INFORMATION PHONE NUMBER: 1-800-729-9029

DATE OF PREPARATION: 07/29/03

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS NUMBER	DESCRIPTION	%	PPM	TLV	LEL	VAPOR PRESSURE
13463-67-7	TITANIUM DIOXIDE	25.3				
9010-88-2	ACRYLIC RESIN*	26.0				
1330-20-07	XYLOL	45.5	100		1%	21@100F

\*= SARA TITLE III 313 REPORTING FOR SUPEFUND AMENDMENTS

### SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

APPEARANCE AND ODOR:	OPAQUE LIQUID WITH AROMATIC SOLVENT ODOR
BOILING RANGE:	231 F – 282 F
VAPOR DENSITY:	HEAVIER THAN AIR
EVAPORATION RATE:	SLOWER THAN ETHER
SOLUBILITY IN WATER:	INSOLUBLE
WEIGHT PER GALLON:	9.0 LBS
% VOLATILITY BY VOLUME:	66

### SECTION IV – FIRE AND EXPLOSION DATA

DOT CATEGORY: FLAMMABLE LIQUID  
FLASH POINT: 40 F  
LEL: 1%  
EXTINGUISHING MEDIA: CO-2, DRY CHEMICAL, FOAM, FOG  
UNUSUAL FIRE AND EXPLOSION HAZARDS: DO NOT USE DIRECT STREAM OF WATER, PRODUCT WILL FLOAT AND CAN BE RE-IGNITED ON SURFACE. VAPORS ARE HEAVIER THAN AIR AND MAY ACCUMULATE IN LOW OR UN-VENTED AREAS.  
SPECIAL FIRE FIGHTING PROCEDURES: DO NOT ENTER FIRE SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT, INCLUDING NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

---

**SECTION V – REACTIVITY DATA**

---

STABILITY:  
STABLE

HAZARDOUS POLYMERIZATION  
WILL NOT OCCUR

INCOMPATIBILITY/ MATERIALS TO AVOID:  
STRONG OXIDANTS LIKE CHLORINE, CONCENTRATED OXYGEN, SODIUM OR CALCIUM HYPOCHLORITE.

HAZARDOUS DECOMPOSITION PRODUCTS:  
FUMES, SMOKE AND CARBON MONOXIDE, IN THE CASE OF INCOMPLETE COMBUSTION.

---

**SECTION VI – HEALTH HAZARD DATA**

---

THRESHOLD LIMIT VALUE:  
100 PPM FOR 8 HOUR WORK DAY RECOMMENDED

EFFECTS OF OVEREXPOSURE:  
INHALATION OF HIGH VAPOR CONCENTRATIONS MAY HAVE RESULTS RANGING FROM DIZZINESS AND HEADACHES TO UNCONSCIOUSNESS. IF BREATHING IS IRREGULAR OR STOPPED, START RESUSCITATION, ADMINISTER OXYGEN. IF INGESTED DO NOT INDUCE VOMITING-CONTACT PHYSICIAN IMMEDIATELY. IN CASE OF SKIN CONTACT, REMOVE ALL CONTAMINATED CLOTHING AND WASH SKIN WITH SOAP AND WATER THOROUGHLY, IF SPLASHED INTO EYES, FLUSH EYES WITH CLEAR WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES-CONTACT A PHYSICIAN.

---

**SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE**

---

VENTILATION: ACE VELOCITY > 60 FPM

PROTECTIVE GLOVES: RECOMMENDED FOR PROLONGED OR REPEATED CONTACT. USE CHEMICAL RESISTANT GLOVES IF NEEDED TO AVOID PROLONGED SKIN CONTACT.

EYE PROTECTION: SAFETY GLASSES WITH UN-PERFORATED SIDE-SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:  
USE CHEMICAL RESISTANT APRON OR OTHER CLOTHING IF NECESSARY TO AVOID REPEATED OR PROLONGED SKIN CONTACT.

MECHANICAL: USE EXPLOSION PROOF EQUIPMENT.

SPECIAL: USE ONLY WITH ADEQUATE VENTILATION EQUIVALENT TO OUTDOORS. NO SMOKING OR OPEN LIGHTS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:  
USE ADEQUATE VENTILATION EQUIVALENT TO THE OUTDOORS. KEEP CONTAINERS CLOSED WHEN NOT

IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, OR STRONG OXIDENTS. USE DURING PREGNANCY SHOULD BE AVOIDED. MAY CAUSE HARM TO DEVELOPING FETUS.

OTHER PRECAUTIONS:

AVOID BREATHING VAPORS AND PROLONGED OR REPEATED CONTACT WITH SKIN. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. REMOVE CONTAMINATED SHOES AND DRY THOROUGHLY. WASH WITH SOAP AND WATER AFTER SKIN CONTACT.

---

---

**SECTION VIII – CONTROL MEASURES**

---

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING OF VAPORS AND VENTILATE EQUIVALENT TO OUTDOORS. REMOVE WITH INERT, ABSORBENTS SUCH AS SAND, EARTH OR SAWDUST, ETC. ADVISE AUTHORITIES IF ANY PRODUCT ENTERS SEWERS, WATERCOURSES, OR LAND AREAS.

WASTE DISPOSAL METHOD:

DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS REGARDING HAZARDOUS POLLUTION. IF DISCARDED, THIS PRODUCT MAY BECOME AN IGNITABLE HAZARDOUS WASTE.

---

---

**SECTION IX - DISCLAIMER**

---

---

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY HOMAX PRODUCTS, INC. TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THESE PRODUCTS OR THE INFORMATION PROVIDED HERewith.